



## NOSTOARVOT TUETTUNA, NOSTOSEKTORI 360°

Nosto- säde m	10.2 m	17.1 m	17.1 m	24.1 m	31 m	35.2 m	38 m	Tukematta takaa		Nosto- säde m
								10.2 m	17.1 m	
3	50									
3.5	45							14		3.5
4	43							12.7	11.5	4
4.5	38.5							11.6	10.6	4.5
5	34.5	28		18.7				10.6	9.7	5
6	28.8	25	20	18.3	10.8	8.7		9	8.1	6
7	25	22.5	20	17.5	10.7	8.6	7.5	8.7	6.8	7
8		20.4	20	16.5	10.6	8.5	7.4		5.7	8
9		16.4	18.2	15.4	10.3	8.4	7.3		4.9	9
10		13.4	15.2	14.4	9.9	8.3	7.2		4.2	10
12		9.4	11	10.8	8.9	7.9	6.9		3	12
14		6.8	8.4	8.2	8.1	7.3	6.4		2.1	14
16				6.5	6.6	6.6	5.7			16
18				5.2	5.3	5.3	5.3			18
20				4.2	4.3	4.3	4.4			20
22					3.5	3.5	3.6			22
24					2.8	2.9	2.9			24
26					2.3	2.3	2.4			26
28					1.8	1.9	1.9			28
30						1.5	1.5			30
32						1.2	1.2			32
34							0.8			34

## RISTIKKOJATKEEN NOSTOKYVYT

Nosto- säde m	Pääpuomin pituus						Pääpuomin pituus						Nosto- säde m
	35.2 m			38 m			35.2 m			38 m			
	Ristikkojatke 0°						Ristikkojatke 20°						
	5.2 m	9 m	16 m	5.2 m	9 m	16 m	5.2 m	9 m	16 m	5.2 m	9 m	16 m	
8	5.7	5		4.5	4		4.3			3.45			8
9	5.7	5	3	4.5	3.95	2	4.25			3.35			9
10	5.65	5	2.9	4.5	3.92	2	4.15	3.6		3.25	3		10
12	5.55	4.9	2.7	4.5	3.9	2	4	3.45	1.8	3.15	2.8	1.75	12
14	5.4	4.7	2.55	4.35	3.85	1.98	3.9	3.3	1.72	3	2.65	1.72	14
16	4.9	4.4	2.4	4.05	3.75	1.96	3.75	3.2	1.65	2.9	2.5	1.7	16
18	4.55	4.1	2.2	3.8	3.5	1.93	3.65	3.05	1.57	2.8	2.35	1.65	18
20	4.3	3.8	2.05	3.55	3.25	1.9	3.55	2.95	1.52	2.75	2.25	1.6	20
22	3.5	3.6	1.9	3.3	3.05	1.85	3.4	2.9	1.46	2.7	2.1	1.55	22
24	2.9	3.1	1.8	2.8	2.85	1.8	2.85	2.8	1.42	2.6	2	1.5	24
26	2.3	2.6	1.7	2.3	2.5	1.7	2.35	2.6	1.4	2.4	1.9	1.45	26
28	1.9	2.15	1.6	1.9	2	1.65	1.85	2.1	1.35	2	1.8	1.42	28
30	1.5	1.8	1.55	1.5	1.65	1.6	1.5	1.7	1.3	1.6	1.75	1.4	30
32	1.2	1.5	1.5	1.2	1.35	1.5	1.2	1.4	1.25	1.3	1.5	1.35	32
34	0.9	1.2	1.4	0.9	1.1	1.3	0.95	1.1	1.17	1	1.2	1.25	34
36	0.6	0.95	1.1	0.6	0.9	1.1	0.7	0.85	1.05	0.7	0.95	1.15	36
38		0.7	0.9		0.7	0.9		0.6	0.9		0.7	0.95	38
40			0.7			0.7			0.65			0.7	40

Nostoarvot perustuvat DIN 15019.2 standardiin.

